



# MAXWELLON MXEMC

4kHz to 40GHz  
EMC System Power Amplifier  
2023

MXEMC EMC System Power Amplifier utilizes GaN power transistors and wideband power matching synthesis technology. The instrument features a single knob for controlling power output, and the front panel includes a 3.5-inch high-brightness LCD screen indicating the output power value. Due to the implementation of Automatic Level Control (ALC) technology, the output power remains nearly constant even when there are variations in the input power. This ALC technology also contributes to a very flat frequency response over a frequency range greater than multiple octaves. Multiple fans on the rear panel ensure continuous and reliable operation of the instrument.

## ■ Key Feature

- **GaN Power Transistors:** The use of Gallium Nitride (GaN) power transistors enhances the amplifier's performance, providing efficient and high-power amplification.
- **Wideband Power Matching Synthesis Technology:** This technology allows the amplifier to cover a broad frequency range while maintaining optimal power matching, ensuring consistent performance across different frequencies.
- **Single-Knob Control:** The instrument is designed with user-friendly controls, including a single knob for adjusting power output. This simplifies operation and enhances ease of use.
- **ALC Technology:** Automatic Level Control (ALC) technology ensures that the output power remains nearly constant, even in the presence of variations in input power. This contributes to stable and reliable performance.
- **High-Brightness LCD Screen:** The front panel features a 3.5-inch high-brightness LCD screen, providing clear and easy-to-read information about the output power.
- **Flat Frequency Response:** The ALC technology contributes to a very flat amplitude-frequency response over a wide frequency range, making the amplifier suitable for applications that span multiple octaves.
- **Reliable Cooling System:** The presence of multiple fans on the rear panel ensures effective cooling, allowing the amplifier to operate continuously and reliably.
- **Versatile Applications:** The amplifier is designed for applications in Electromagnetic Compatibility (EMC) testing, where its wide frequency coverage and stable performance are critical.

## ■ Specification

Model	Min	Max	Gain (dB)	Output Power (W)	Gain Flatness (±dB)	VSWR	Connector	Operating Voltage
MXEMC-000400M-1000W	4KHz	400MHz	50~65	1000W	±3.0	≤2.0	N-K	AC380
MXEMC-000100M-5000W	10KHz	100MHz	50~67	5000W	±3.0	≤2.0	N-K	AC380
MXEMC-000400M-2000W	10KHz	400MHz	50~67	2000W	±3.0	≤2.0	N-K	AC380
MXEMC-008010G-3000W	80MHz	1000MHz	50~65	3000W	±3.0	≤2.0	N-K	AC380
MXEMC-007060G-200W	700MHz	6GHz	40~53	200W	±3.0	≤2.0	N-K	AC220
MXEMC-010060G-1000W	1GHz	6GHz	40~60	1000W	±3.0	≤2.0	N-K	AC380
MXEMC-060180G-500W	6GHz	18GHz	40~57	500W	±3.0	≤2.0	N-K	AC380
MXEMC-180265G-200W	18GHz	26.5GHz	40~53	200W	±3.0	≤2.0	N-K	AC380
MXEMC-265400G-200W	26.5GHz	40GHz	40~53	200W	±3.0	≤2.0	N-K	AC380



**Maxwellon Electronic Instruments Co.,LTD.**

Factory: No.6 Xiangjiang Road, Qingdao 266000, China  
Tel: 0086 13816527810

Sales Office: NO.153 Zhuzhou Rd.,Laoshan District, Qingdao 266100, China.  
Tel: 0086-532-80977508  
Fax: 0086-532-80977508

Sales: [Sales@Maxwellon.com](mailto:Sales@Maxwellon.com)  
Web: [www.maxwellon.com](http://www.maxwellon.com)